

YS-0.25/YS-0.6 Piston Pressure Vacuum Gauge

The type piston pressure vacuum gauge is mainly used to inspect the 0.16, 0.25 and 0.4 precision pressure gauges in the range of -0.1~0.25MPa to -0.1~0.6MPa. The accuracy level of the pressure gauge is 0.05 or 0.02, and the working medium is gas.

Measuring range: -0.1~0~+0.25MPa, -0.1~0~+0.6MPa;

Accuracy level: 0.05 level, 0.02 level;

Working medium: clean compressed air or bottled nitrogen;

Connection thread: M20*1.5 quick connector;

Weight material: grade 0.05 is carbon steel weight, grade 0.02 is non-magnetic stainless steel weight;

Verification standard: "JJG99-2006 National Metrological Verification Regulations for Weights";

"JJG236-2009 Verification Regulation of Piston Pressure Vacuum Gauge";

Name	Unit	YS-0.25	YS-0.6
Upper limit of measurement	Mpa	0.25	0.6
Lower limit of measurement	Mpa	0.005	0.005
Range	Mpa	-0.1~-0.005, +0.005~0.25	-0.1~-0.005, +0.005~0.6
Weights	Mpa*pcs	0.05*3pcs,0.02*7pcs 0.01*3pcs,0.005*2pcs	0.05*7pcs,0.02*7pcs 0.01*3pcs,0.005*2pcs
Lock nuts		M20*1.5	M20*1.5
Weight	KG	30	35
Working medium		Clean compressed air or bottled nitrogen	